

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME  
MARTIN-SENOUR AUTOMOTIVE SALES  
5422 Dansher Road  
Countryside, Illinois 60525  
DATE OF PREPARATION  
8-Feb-88

EMERGENCY TELEPHONE NO.  
(216) 566-2917  
INFORMATION TELEPHONE NO.  
(216) 566-2902

Acrylic Lacquer Thinner

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet. If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention. If SWALLOWED: Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give several glasses of water. Seek medical attention.

CHRONIC Health Hazards

Methyl Ethyl Ketone may increase the nervous system effects of other solvents. Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, blood forming, cardio-vascular, and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI -- REACTIVITY DATA

STABILITY -- Stable

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION -- Will Not Occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section I -- PRODUCT IDENTIFICATION

Trade Mark

Section II -- HAZARDOUS INGREDIENTS

CAS NO.	INGREDIENT	% by WEIGHT	ACGIH-TLV	OSHA-PEL	UNITS	V.P.
64742-89-8	Lt. Aliphatic Hydrocarbon Solvent.	5-15	100	500	PPM	53.0
64742-48-9	V. M. & P. Naphtha.	0-10	300	200	PPM	12.0
108-88-3	Toluene.	20-55	100	200	PPM	22.0
67-56-1	Methanol	<5	200	200	PPM	92.0
67-63-0	2-Propanol	5-10	400	400	PPM	33.0
78-83-1	2-Methyl-1-propanol	<5	50	100	PPM	8.7
67-64-1	Acetone.	10-20	750	1000	PPM	180.0
78-93-3	Methyl Ethyl Ketone.	0-5	200	200	PPM	70.0
108-10-1	Methyl Isobutyl Ketone.	0-5	50	100	PPM	16.0
123-86-4	n-Butyl Acetate.	0-25	150	150	PPM	10.0
108-65-6	1-Methoxy-2-Propanol Acetate	<5	Not Established			1.8

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen

For specific percent hazardous ingredients in each product, see Section X

Section III -- PHYSICAL DATA

EVAPORATION RATE -- Slower than Ether	VAPOR DENSITY -- Heavier than Air
BOILING RANGE 132-325 F	VOLATILE VOLUME 100.0 %
	WT/GAL 6.80 lb.

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION FLASH POINT 4 F TCC LEL 0.9

RED LABEL -- Extremely Flammable, Flash below 21 F

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Continued on page 1

Continued on page 3

Acrylic Lacquer Thinner

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust mask or particulate respirator.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY -- 1B

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame.

Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke -

Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and

appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section X -- PERCENT HAZARDOUS INGREDIENTS

	3092	3099	CA3099
Lt. Aliphatic Hydrocarbon Solvent.	15	5	10
V. M. & P. Naphtha.	--	--	10
Toluene.	50	55	20
Methanol	<5	<5	<5
2-Propanol	<5	<5	10
2-Methyl-1-propanol	<5	<5	<5
Acetone.	20	20	10
Methyl Ethyl Ketone.	--	--	5
Methyl Isobutyl Ketone.	<5	5	--
n-Butyl Acetate.	--	--	25
1-Methoxy-2-Propanol Acetate	<5	<5	<5

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

HMS

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0